



Wax Bowl Ring Specification Sheet

Product: **Reinforced Wax Bowl Ring Kit**
Code: **WR-03A**

Description: Wax Bowl Ring reinforced with Urethane. Includes Polypropylene Flange and a package of all-brass bolts. Quick, easy to install. Forms a gas-tight, odor-tight, water-tight seal. Will not harden or deteriorate. Adjusts to contraction, expansion and settling of floors. Leaves no unsightly oil stains. Meets Federal Spec. TT-P-1536A.



WAX PARAMETERS	Method	Specification
Melting Point	ASTM D-127	152°F Min
Color	ASTM D-1500	4.5 Max
Penetration @ 77°F	ASTM D-937	67-75 dmm
Pouring Test @150°F	MA-CC8-35	Pass
Bend Test @32°F	MA-CC8-27	Pass

RING DIMENSIONS

Wax Bowl Ring Weight	170 gr (6 oz) Min
Thickness	22 mm (0.86 in)
External Diameter	132 mm (5.2 in)
Internal Diameter	92 mm (3.62 in)

PACKAGING MATERIAL

1. Individual Box:	
Material	Clay Coated Paperboard
Outside Dimensions	5 7/8 in x 5 7/8 in x 2 in
Caliper	0.018 in
Printing Colors	Depending on Design
2. Master Carton:	
Material	Kraft
Outside Dimensions	12.5 In x 12.5 in x 12.5 in
Bursting Test (lbs/in ²)	12.5
Printing	Product & Customer Info

PACKAGING INFORMATION

Case Pack	24 pieces.
Case Weight	6.62 kg (14.59 lb)
Cases per Pallet	54 cases
Cases per Layer	9 cases
Layers per Pallet	6 layers
Pieces per Pallet	1,296 pieces.
Pallet Preparation	Paper corner reinforcements, stretch wrapping

SHIPPING INFORMATION

Pallet Size	38 in x 38 in x 6 ft 9 in
Pallet Weight	372.48 kg (821.17 lb)
Pallets per Truck	32 pallets

Artwork for private labeling: To be submitted by customer in Illustrator or Freehand format.
Media: 3.5" diskette, CD ROM. Media should be accompanied by signed printout.